



Clear Lacquer M-6009 Satin W.W.

320 Paterson Plank Road
Carlsadt, NJ 07072
Tel 800-426-0496
201-933-1000
Fax 201-933-3646

Product Description

Satin W.W. Compliant Cold Spray Lacquer

Recommended Uses

Fine finishing of wood furniture, architectural woodwork, musical instruments, picture frames and other decorative accessories.

Benefits

Appearance:

- Excellent film clarity.
- Non-yellowing.

Production.

- Excellent build.
- No reduction - ready to spray.
- Very fast drying.
- High solids by weight and volume.
- High spreading rate.
- Achieves smooth finish with conventional spray equipment at room temperature
- Easy to repair.
- Compliant with state and federal EPA standards.

Surface Preparation

All contaminants, oil, grease and loose dirt must be removed, and all surfaces must be completely dry prior to mating.

Wood surfaces must be sanded smooth with the grain, and surface blemishes must be corrected. All surfaces must be free from grease and other foreign matter, and completely dry prior to coating.

Application

Stain

QD Wiping Stain and or NGR

Stain, Filler, Barrier Filler (if applicable)

Use Seagrave Natural or Pigmented Filler

Sealer

Use M-5465 EPA Compliant Sealer. Sand with 320 Grit Stearated Paper

Washcoat

For open grain use 282 EPA Compliant Washcoat

Reduction

Can be applied 'as is'.

continued