



_(CONLAC) PRECATALYZED CLEAR SATIN LACQUER 25° F-124100

PRODUCT DESCRIPTION

25° High gloss precat clear proprietary lacquer.

RECOMMENDED USES

Kitchen cabinets, office furniture, healthcare, schools, hotels and other high-use applications.



BENEFITS

- Ease of application, self seal, dry time, and recoatability of nitrocellulose lacquer, but with higher solids and improved household chemical resistance.
- High durability.
- Very good scratch and mar resistance.
- Normal household dirt and stains can be cleaned with soap and water.
- Excellent adhesion.
- Conforms with AWI Finish System TR-2.
- VOC compliant in NY and NJ area.
- Conforms to NKCA standards.

APPLICATION

Can be applied by all conventional or HVLP spray methods. Use Sealer #939504 or as a self seal product.

SPECIFICATIONS

Color...... Water White

Gloss...... 25° ± 3%

Viscosity...... #2 Zahn Cup
23 ± 1 seconds 77°F

Density...... 7.45 lbs/gal ± 0.1

Solids By Weight...... 22% ± 1%

Solids By Volume...... 15% ± 1%

VOC...... 4.63 lbs/gal 555 gms/lit

Coverage...... 240 sq. ft. lb 1.0 mils
dry film thickness

Recommended Dry...... 1.5 - 2 mils
Film Thickness