



_(CONLAC6) PRECATALYZED LACQUER CLEAR HIGH GLOSS F-124110

PRODUCT DESCRIPTION

High gloss precat clear proprietary lacquer.

RECOMMENDED USES

Kitchen cabinets, office furniture, healthcare, schools, hotels and other high-use applications.



BENEFITS

- Ease of application, self seal, dry time, and recoatability of nitrocellulose lacquer, but with higher solids and improved household chemical resistance.
- High durability.
- Very good scratch and mar resistance.
- Normal household dirt and stains can be cleaned with soap and water.
- Excellent adhesion.
- Conforms with AWI Finish System TR-2.
- VOC compliant in NY and NJ area.
- Conforms to NKCA standards.

APPLICATION

Can be applied by all conventional or HVLP spray methods. Use Sealer #939504 or as a self seal product.

SPECIFICATIONS

Color..... Water White

VOC..... 4.67 lbs/gal 560 gms/lit

Gloss..... 85 $\pm$ 3%

Viscosity..... #2 Zahn Cup-
23 $\pm$ 2 seconds @ 77°F

Coverage..... 270 sq. ft. 1.0 mils
dry film thickness

Density..... 7.40 lbs/gal $\pm$ 0.1

Recommended Dry..... 1.5 - 2 mils
Film Thickness

Solids By Weight..... 24% $\pm$ 1%

Solids By Volume..... 17% $\pm$ 1%